

Pneumatic Tyre Changer with Tilting Column

This tyre changer features a pneumatically operated tilting column and simultaneous pneumatic horizontal and vertical arm locking. It is capable of handling stiff, wide, and low-profile tires.



Product Overview

Professional Pneumatic Tyre Changer

The U-226A is a high-performance pneumatic tyre changer designed to streamline tyre servicing in busy automotive workshops. Featuring a robust tilting column and a high-power motor, it handles wheels with precision and ease. Its ergonomic control interface is designed to maximize operator productivity while the pneumatic bead breaker ensures efficient tyre removal and installation.

Performance Specifications

Key Performance Metrics

2500 kg

Bead Breaker Force

8 bar

Required Air Supply

70 dB

Max Noise Level

Motor Power Options

0.75kw, 0.55kw, 1.1kw

Capacity

Wheel Dimensions

Parameter	Value
Max Wheel Diameter	41" (1040mm)
Max Wheel Width	14" (355mm)
Outside Clamping	10"-22"
Inside Clamping	12"-24"

Equipment Logistics

Equipment Weight

277kg / 297kg

Standard Accessories

Included Components

- Cast steel pedal set
- Combined bead pressing device
- Complete aluminium alloy pedal
- Mounting and demounting head
- Bead lifting tool

Optional Add-ons

Available Upgrades

Motorcycle adaptor • Clamp protector • Mounting head • Plastic mounting head protector • Bead breaker blade protector