

Polyester Webbing Sling

This flat lifting belt is made of 100% PES and can be used with ring eye or metal parts to improve strength. It provides a broad, smooth bearing surface, especially beneficial when lifting soft surfaces where contact with metal is undesirable.



ADDITIONAL IMAGES



Overview

High-Strength Polyester Webbing Sling

This flat lifting belt is crafted from 100% high-strength polyester (PES) for exceptional durability and load-bearing performance. Designed for industrial lifting, it features a flat, wide surface that provides stability and reduces the risk of surface damage to delicate loads. The sling is available in a wide range of capacities from 0 to 50 tons and lengths from 1 to 100 meters, featuring reinforced lifting eyes for secure and reliable attachment.

Technical Specifications

Construction Layers

Single Layer • Double Layer

Material	100% High-Strength Polyester (PES)
Load Capacity Range	0 - 50 tons
Length Range	1 - 100 meters
Available Safety Factors	5:1, 6:1, 7:1

Performance Data

Standard Load Capacity Table (EB-B Series)

Model	Straight Lift (kg)	Width (mm)
EB-B-01	1000	25
EB-B-02	2000	50
EB-B-03	3000	75
EB-B-04	4000	100
EB-B-05	5000	125
EB-B-06	6000	150
EB-B-08	8000	200
EB-B-10	10000	250
EB-B-12	12000	300

Key Features

Why Choose This Sling

- Non-damaging to painted or delicate surfaces
- Reinforced lifting eyes for improved strength
- Wide, smooth bearing surface for stability
- Color-coded for easy capacity identification
- Available with various eye folding methods