

Portable 2.2kW Gasoline Generator

This portable gasoline generator delivers reliable power for tools and appliances. It features a fuel-efficient engine, durable frame, and a user-friendly control panel with multiple outlets.

<p>KJ2000A</p> <p>Type: Brush, Revolving Magnetic Field, 2 Poles, Single-phase Frame: 0.25mm Steel Tube Rated AC Output: 2.2kW/200V Max AC Output: 2.5/2.5 kW Frequency: 50/60Hz Voltage: 110~120/220~240V Voltage Regulator: AVR System Power Factor: Cosφ = 1.0</p> <p>Engine Model: A166F-5.5hp Type: Air-cooled, 4-Stroke, OHV, single cylinder Bore × Stroke: 68mm × 54mm Displacement: 166ml Recommended Fuel: Unleaded Gasoline Fuel tank capacity: 16L Fuel consumption: ≤395g/kWhour Engine Oil Capacity: 0.4L Start Mode: Recoil and hand-operated</p> <p>Standard Features</p> <p>Oil Alert: with Fuel Gauge: with AC Voltmeter: with Indicator Light: without AC Circuit Breaker: with Electric Starter: without</p> <p>Option</p> <p>DC socket(12V/8.3A): with DC Circuit Breaker: with</p>
--

ADDITIONAL IMAGES



Overview

Reliable Power Anywhere

The KJ2000A is a versatile, portable gasoline generator engineered for consistent performance across construction sites, camping trips, and emergency backup scenarios. Featuring a robust 5.5HP engine and a durable steel frame, it delivers stable power output with built-in safety mechanisms like an Automatic Voltage Regulator (AVR) and overload protection. This single-phase generator is designed for ease of use, offering multiple power outlets and efficient fuel consumption to ensure extended operational run times.

Performance Metrics

Power Output

2.2 kW Rated AC Output	2.5 kW Max AC Output
----------------------------------	--------------------------------

Electrical Specifications

Parameter	Value
Frequency	50/60 Hz
Voltage	110~120/220~240 V
Power Factor	Cosφ = 1.0
Voltage Regulation	AVR System

Engine Details

Engine Specifications

- Model: A168F
- Power: 5.5 HP
- Type: Air-cooled, 4-Stroke, OHV, Single-cylinder
- Displacement: 196 ml
- Bore x Stroke: 68mm x 54mm
- Start Mode: Recoil and hand-operated

Fuel & Capacity

Fuel & Oil

- Recommended Fuel: Unleaded Gasoline
- Fuel Tank Capacity: 16 L
- Fuel Consumption: d395 g/kW-hour
- Engine Oil Capacity: 0.6 L

Features & Equipment

Standard Features

Oil Alert, Fuel Gauge, AC Voltmeter, AC Circuit Breaker, Brush-type Generator

Optional Equipment

DC Socket (12V/8.3A), DC Circuit Breaker

Construction

Build Quality

Frame constructed from 125mm steel tube for durability and transport protection.