



# PP Spun String Wound Filter Cartridge

This filter cartridge features a honeycomb-like structure for effective removal of suspended solids, particulates, and rust from liquids. The polypropylene string wound design ensures high-quality filtration.



## ADDITIONAL IMAGES



## Overview

### High-Efficiency Depth Filtration

The PP String Wound filter cartridge is an industrial-grade depth filter engineered for the high-capacity removal of sediments, rust, dirt, and sand. Constructed with a robust polypropylene core and precision-wound fibers, it provides exceptional dirt-holding capacity and consistent flow rates. Its versatile material compatibility and wide range of configurations make it an ideal choice for protecting sensitive processes across the microelectronics, beverage, and petrochemical industries.

## Technical Specifications

### Dimensions

Parameter	Range/Value
Outer Diameter	50-120 mm
Inner Diameter	28/30 mm
Length	5/10/20/30/40 inch

### Key Performance Indicators

**4.2 bar**

Max Differential Pressure

**0.6 m<sup>2</sup>**

Filtration Area (10 inch)

### Pore Size Range

0.5 - 100  $\mu$ m

## Materials and Compatibility

Construction Materials	Polypropylene, Cotton, Glass Fiber, Silicone, Viton, EPDM
PH Resistance	1 - 13

## Operating Conditions

### Maximum Operating Temperatures

- Polypropylene: 80°C (172°F)
- Cotton: 130°C (280°F)
- Glass Fiber: 300°C (645°F)

## Application

### Compatible Industries

Water Purification, Beverage & Wine, Microelectronics, Medicine, Sewage Treatment, Electroplating, Optical, Petrochemical