

Refrigerated Cake Display Case

This cake cabinet features ultra-white heating glass and high-brightness LED lighting for a good display effect. It maintains a refrigeration temperature of 5 after 20 minutes of startup when the ambient temperature is 28-30 .



Overview



Showcasing the multi-tiered display area and energy-efficient lighting design.

Professional Refrigerated Display

This high-performance refrigerated display cabinet features ultra-white heating glass and high-brightness LED lighting to maximize product visibility. Engineered for reliability, it utilizes premium components including an imported compressor and precise temperature controller to ensure rapid cooling. The cabinet maintains a clear view even when doors are opened, effectively preventing fog and condensation to preserve the perfect display effect.

Technical Specifications

Available Models and Dimensions

Model	Cabinet Size (mm)	Packing Size (mm)
SK730A-ME	900x680x1370	1000x780x1470
SK740A-ME	1200x680x1370	1300x780x1470
SK750A-ME	1500x680x1370	1600x780x1470
SK760A-ME	1800x680x1370	1900x780x1470
SK770A-ME	2100x680x1370	2200x780x1470
SK780A-ME	2400x680x1370	2500x780x1470

Performance Metrics

5 min to 5
Cooling Time

2
Min Temperature

8
Max Temperature

Design and Build

Component Brands

- Compressor: Embraco
- Controller: Dixell

Core Features

ITO Heating Glass, LED 6500K Lighting, Sliding Rear Doors, Digital Temperature Control

Logistics and Support

Certifications

CE • RoHS

Warranty and Service

1-2 years warranty with lifelong technical support provided.