

# RG6 Coaxial Cable for Security Cameras

This is a 75ohm single RG6 coaxial cable designed for security camera use. It features a 1.0mm copper-clad steel (CCS) conductor.



## Product Overview

### High-Performance RG6 Coaxial Cable

This RG6 coaxial cable is specifically engineered for high-fidelity video transmission in security camera and CCTV systems. Featuring a 75 Ohm impedance and a robust construction with HD-PE insulation, it ensures minimal signal loss over long distances. The versatile jacket options and reliable shielding make it an ideal choice for professional surveillance installations requiring durable and consistent connectivity.

#### Available Colors

- Grey (Highly Suggested)
- Blue
- Black
- White

## Key Performance Metrics

### Key Performance Metrics

**75 Ohms**

Impedance

**305 m**

Standard Length

**8**

Conductor Count

## Technical Construction

### Jacket Material Options

PVC • PE • LSZH

### Conductor Material

Cu (Copper), TCu (Tinned Copper), CCS (Copper Clad Steel)

### Conductor Diameter

0.08 - 1.66mm

### Insulation Material

HD-PE

## Compliance & Quality

### Certifications

CE, ROHS, ISO

## Logistics & Packaging

### Packaging Specifications

| Unit           | Quantity           |
|----------------|--------------------|
| Standard Box   | 300m per box       |
| Master Carton  | 2 boxes per carton |
| 20ft Container | 1000 boxes         |
| 40HQ Container | 2300 boxes         |

|                |        |
|----------------|--------|
| Package Weight | 15 KGS |
|----------------|--------|

## Supply & Terms

### Accepted Payment Terms

- L/C
- T/T

|                        |                             |
|------------------------|-----------------------------|
| Minimum Order Quantity | 30,000 Meters (100 Cartons) |
|------------------------|-----------------------------|

|           |                          |
|-----------|--------------------------|
| Lead Time | 12-18 days after deposit |
|-----------|--------------------------|