

Rotary Cam Switch

This rotary cam switch is designed for diverse electrical applications. It is rated for high voltage and current applications and features clearly marked terminal connections.



Overview

LW26GS Rotary Cam Switch

The LW26GS series rotary switch is engineered for reliable performance in diverse industrial and commercial electrical applications. Designed for versatility, it functions effectively as a control switch, transfer switch, or motor control switch. The series is available in two distinct configurations: a common type with a black plate and handle, and a quick-stop type featuring a yellow plate and red handle for enhanced visibility and safety.

Technical Specifications

Operational Life

8500 cycles

Non-load Operations

1500 cycles

Load Operations

10000 cycles

Total Operations

Current and Power Ratings

Ith (A)	AC-21A (A)	AC-22A (A)	AC-23A (A)	Power (kW)
20	20	20	15	7.5
25	25	25	22	11
32	32	32	30	15
63	63	63	57	30
125	100	100	90	45
160	150	150	135	75

Rated Working Voltage

440 V

Available Rated Thermal Currents

20A, 25A, 32A, 63A, 125A, 160A

Installation & Mounting

ANDELI **LW26GS**

LW26GS Series Par-lock Type Switches

1. **General Information**

2. **Technical Specifications**

Model	Current Rating (A)	Terminal Voltage (V)	Terminal Voltage (V)	Terminal Voltage (V)	Terminal Voltage (V)
LW26GS10	10	250	250	250	250
LW26GS15	15	250	250	250	250
LW26GS20	20	250	250	250	250
LW26GS25	25	250	250	250	250
LW26GS32	32	250	250	250	250
LW26GS63	63	250	250	250	250
LW26GS125	125	250	250	250	250
LW26GS160	160	250	250	250	250

3. **Dimensions and Installation (Dimension Unit: mm)**

Model	Dimension A	Dimension B	Dimension C	Dimension D	Dimension E	Dimension F	Dimension G	Dimension H	Dimension I	Dimension J	Dimension K	Dimension L	Dimension M	Dimension N	Dimension O	Dimension P	Dimension Q	Dimension R	Dimension S	Dimension T	Dimension U	Dimension V	Dimension W	Dimension X	Dimension Y	Dimension Z	
LW26GS10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
LW26GS15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15
LW26GS20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
LW26GS25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
LW26GS32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32
LW26GS63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
LW26GS125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125
LW26GS160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160

Overview of available current ratings and compatible mounting plates for the LW26GS series.

Compatible Escutcheon Plates

- M1 (20A, 25A)
- M2 (20A, 25A, 32A, 63A)
- M3 (32A, 63A, 125A, 160A)

Design Options

Available Configurations

Common Type (Black Plate/Handle) • Quick Stop Type (Yellow Plate/Red Handle)