

# Single Eye Standard Duty Cable Support Grip

These standard closed mesh support grips are designed for loads up to 600lbs and vertical runs of no more than 100ft. The wire mesh is produced from high-quality, non-magnetic, tin-coated bronze, providing superior corrosion resistance.



## Product Overview



Standard duty support grip featuring a single eye attachment point for vertical cable runs.

### Standard Duty Single Eye Support Grip

This standard closed-mesh support grip is engineered for reliable load management in vertical cable runs. Constructed from high-quality, non-magnetic, tin-coated bronze, it offers superior corrosion resistance while effectively absorbing strain from vibration, expansion, and flexing. The single-eye design is specifically optimized for vertical applications where the cable needs to bend, making it an ideal solution for electrical, fiber optic, and industrial tubing support.

## Key Features

### Key Features

- Supports loads up to 600 lbs
- Suitable for vertical runs up to 100 ft
- Non-magnetic, tin-coated bronze construction
- Superior corrosion resistance
- Absorbs strain from vibration and expansion
- Single eye design for vertical applications with cable bends

## Technical Specifications

### Max Load Capacity

**600 lbs**

Max Load

**100 ft**

Max Vertical Run

### Material

Tin Coated Bronze • Non-Magnetic

## Product Data Table

### Model Specifications

| Part Number | Cable Diameter           | Bale Length  | Mesh Length   | Break Strength |
|-------------|--------------------------|--------------|---------------|----------------|
| HGPL1216    | 0.50-0.61" (12.7-15.5mm) | 7" (177.8mm) | 11" (279.4mm) | 770 lbs        |
| HGPL1519    | 0.62-0.74" (15.7-18.8mm) | 8" (203.2mm) | 11" (279.4mm) | 960 lbs        |