

Soft Sealing Plug Valve

This soft sealing plug valve is designed with AWWA c517 Standard. It features a spherical body and a cylindrical plug with a soft sealing material, ensuring tight shutoff and minimal leakage.



Product Overview

Industrial Soft Sealing Plug Valve

This robust plug valve features an eccentric structural design and a circular channel to provide excellent flow characteristics and energy efficiency. Engineered for durability, it utilizes a ductile iron body with internal and external epoxy resin coating for superior corrosion resistance. The valve ensures reliable, bi-directional sealing with a nitrile rubber-wrapped core and a self-adjusting U-shaped sealing ring, making it an ideal choice for petrochemical, water treatment, and power applications.

Technical Specifications

| | |
|------------------------|--------------------|
| Nominal Diameter Range | 1/2 inch - 24 inch |
| Max Temperature | 212 °F |
| Suitable Media | Water |

Performance Metrics

Pressure Ratings

175 psi

1/2"-12" Pressure

150 psi

14"-24" Pressure

Construction & Design

Key Materials

- Ductile iron body, bonnet, and spool
- Nitrile rubber wrapped valve core
- Pure nickel valve seat surfacing
- Stainless steel embedded radial shaft sleeve

Design Features

- Eccentric design for quick opening
- Open design valve body cover for maintenance
- Self-adjusting U-shaped sealing ring
- Bi-directional valve performance
- Epoxy resin anti-corrosion coating

Compliance & Standards

| | |
|-----------|------------------------------|
| Standards | AWWA C517, ANSI B16.1 Flange |
|-----------|------------------------------|