


SS316 Stainless Steel Type E Camlock Hose Coupling

This SS316 camlock fitting is suitable for use with salt water, water waste, chemicals, hydraulic oil, and coolants. The quick coupling features excellent corrosion resistance, high temperature capability, and a long life expectancy.



ADDITIONAL IMAGES



Product Overview

High-Performance Type E Camlock Coupling

The SS316 Stainless Steel Type E Camlock Coupling provides a secure and reliable solution for fluid transfer across industrial, chemical, and agricultural applications. Engineered from high-grade 316 stainless steel, this fitting offers exceptional corrosion resistance and a broad operating temperature range from -150°F to +500°F. Designed for efficiency, the male adapter with hose shank enables quick connection and disconnection, ensuring long service life and performance in demanding environments.

Technical Specifications

Thread Types

- NPT
- BSPP
- BSPT

Seal Options

- NBR
- BUNA
- EPDM
- VITON

Material	SS316 Stainless Steel, SS304 Stainless Steel
Standards	A-A-59326, DIN 2828
Size Range	1/2" to 8"
Temperature Range	-150°F to +500°F

Performance Metrics

Working Pressure by Size

250 PSI

3/4" - 2"

225 PSI

2-1/2"

200 PSI

3" - 4"

150 PSI

6"