

Stainless Steel Camlock Coupling

These stainless steel camlock couplings provide secure and leak-proof connections for fluid transfer. They offer excellent corrosion resistance and are suitable for a wide range of media, including water, chemicals, and petroleum products.



ADDITIONAL IMAGES



Product Overview

High-Performance Stainless Steel Camlock Couplings

These stainless steel camlock couplings are precision-engineered for secure, leak-proof connections in demanding fluid transfer applications. Designed for superior corrosion resistance and high-temperature performance, they are compatible with water, wastewater, chemicals, hydraulic oil, and coolants. Their robust construction ensures a long service life and reliable quick-connect functionality across various industrial settings.

Technical Specifications

Materials	Stainless Steel 316, Stainless Steel 304
Available Sizes	1/2" to 8"
Standards	A-A-59326, DIN 2828

Performance Metrics

Working Pressure Ratings

Size Range	Pressure
3/4" - 2"	250 PSI (17.6 bar)
2 1/2"	225 PSI (15.8 bar)
3" - 4"	200 PSI (14.8 bar)
6"	150 PSI (10.5 bar)

Working Temperature	-150°F to +500°F
---------------------	------------------

Components

Seal Options	NBR, BUNA, EPDM, VITON
Handle and Pin Material	Carbon steel plated, Stainless steel, Brass