

Stainless Steel L-Type Banding Buckle

This L-type locking buckle is made from uncoated stainless steel. It offers strong tensile strength and corrosion resistance for banding applications.



Product Overview

Product Display

Durable L-type buckle designed for secure tensioning and banding applications.

Professional L-Type Banding Buckle

This L-type locked banding buckle is engineered for high-performance fastening in demanding industrial environments. Constructed from high-quality, uncoated stainless steel, it offers superior corrosion resistance and exceptional tensile strength. The specialized L-type design ensures a reliable, slip-resistant locking mechanism, making it an ideal solution for secure cable management and heavy-duty hose clamping.

Technical Specifications



Uncoated stainless steel construction provides long-lasting performance in various environments.

Model Specifications

Model	Width (in/mm)	Thickness (mm)	Packing Qty
TSBL-8	1/4 (8)	0.7	100
TSBL-10	3/8 (10)	0.7	100
TSBL-12.7	1/2 (12.7)	0.7	100
TSBL-16	5/8 (16)	0.7	100
TSBL-19	3/4 (19)	0.9	100

Material Properties

Acid-proof, Corrosion-resistant, High-tensile strength, Uncoated Stainless Steel

Key Features

Operational Advantages

- Easy and fast operation for increased efficiency
- Secure L-type locking mechanism prevents slippage
- Excellent for indoor and outdoor industrial applications
- Reliable tension retention