

Submersible Sewage Pump for Wastewater Handling

This submersible sewage pump is engineered for durable and reliable operation in demanding environments. It is suitable for wastewater management, drainage, and effluent transfer applications.



Product Overview

High-Efficiency Submersible Sewage Pump

This submersible sewage pump is engineered for robust performance in demanding wastewater management tasks. Its compact and versatile design allows for both temporary and permanent installations, making it an ideal choice for residential, commercial, and industrial sites. With options ranging from single-phase to three-phase power configurations, it ensures reliable operation in varied sewage and wastewater applications.

Key Features

Applications

Wastewater Management, Sewage Handling, Restaurant Systems, Hotel Infrastructure, Camping Sites, Effluent Transfer

Technical Specifications

Performance Data

Model	Flow (m ³ /h)	Head (m)	Power (kW)	Voltage (V)
WQASD7-12-0.9	7	12	0.9	220V
WQASD7-16-1.2	7	16	1.2	220V
WQAS7-12-0.9	7	12	0.9	380V
WQAS7-16-1.2	7	16	1.2	380V
WQAS7-21-1.5	7	20	1.5	380V
WQAS7-28-2.6	7	28	2.6	380V
WQAS8-31-3.1	8	31	3.1	380V
WQAS10-38-4	10	38	4	380V

Common Parameters

2900 RPM

Speed

40 mm

Outlet Diameter

50 Hz

Frequency

Installation Details

Installation Options

- Auto-coupling system
- Free-standing on pit bottom