


Submersible Water Transfer Pump

This submersible pump is designed for efficient water transfer. It is suitable for applications such as dewatering basements and draining ponds.



ADDITIONAL IMAGES



Product Overview

Compact Submersible Performance

This submersible water transfer pump is engineered for continuous operation in demanding marine and freshwater environments. Its compact, lightweight design combines high delivery volume with a specialized motor cooling system and double mechanical seal for enhanced durability. Constructed with 304 stainless steel and corrosion-resistant materials, it provides a reliable solution for drainage, emergency pumping, and water circulation tasks.

Technical Specifications

Core Performance

70 L/min

Delivery Volume

4 m

Delivery Head

45 W

Motor Power

Model Specifications

Feature	BL2524S	BL2512S
Voltage	DC 24V	DC 12V
Current	2.5A	5.4A

Physical Dimensions

- Outlet Diameter: 25mm (1 inch)
- Weight: 1.3kg
- Operating Temperature: 0-60°C

Features and Compliance

Suitable Applications

- Bilge water discharge
- Boat emergency pumping
- Fish farm water exchange
- Deck washing
- Camping and car washing
- Freshwater preserve pumping

Design Advantages

Continuous Operation, Double Mechanical Seal, Tool-Free Strainer, 304 Stainless Steel, Saltwater Resistant