

Surface Mounted 1 Gang 2 Way Light Switch

This surface mounted switch allows control of a single light from two locations. It features a fire-resistant build and easy installation.



Overview

Professional Surface Mounted Lighting Control

This 1 Gang 2 Way light switch features a simple and sleek design that adapts seamlessly to various decoration styles. Engineered for safety and reliability, it is constructed from fire-resistant PC and PP materials capable of passing 850°C flammability tests. The unit includes a practical LED indicator that glows when the switch is off to provide guidance in the dark, making it an ideal choice for hotels, hospitals, and residential applications.


Technical Performance

Electrical Specifications

250 V~ Rated Voltage	10 AX Rated Current	2500 W Max Power
--------------------------------	-------------------------------	----------------------------

Mechanical Endurance	Tested up to 40,000 operations
Rated Frequency	50 Hz

Design & Construction



Sleek, modern design suitable for diverse interior environments.

Dimensions	70mm x 60mm x 30.6mm
Housing Materials	Fire-resistant PC, PP Material
Available Colors	White (Custom colors available on request)

Installation & Application

Recommended Applications

- Hotels and Hospitality
- Hospitals and Healthcare
- Residential Buildings
- Commercial Offices
- Industrial Facilities

Mounting Method

Surface Mounted

Wiring Capacity

Wiring holes match pipe up to $\text{Æ}14$

Compliance & Quality

Quality Standards

CE • ISO 9001 • ISO 14000 • European Standard

Logistics & Customization

Standard Packaging

Unit	Quantity	Dimensions
Inner Bag	1 pc	-
Inner Box	18 pcs	174 x 160 x 150 mm
Master Carton	216 pcs (12 boxes)	480 x 335 x 363 mm

Minimum Order Quantity

3000 pcs

Customization Services

Logo Printing, Custom Color, Bespoke Packaging