


Tie Down Strap Webbing

This webbing sling is produced from high-quality synthetic fiber using advanced weaving technology. It meets international standards for color and load capacity, with safety factors ranging from 4:1 to 8:1 and load ranges from 0.5t to 100t.



ADDITIONAL IMAGES



Product Overview

Industrial-Grade Lifting and Securing Webbing

This high-tenacity polyester webbing is engineered for demanding industrial lifting and cargo restraint applications. Manufactured in accordance with EN1492 standards, the strap offers a high strength-to-weight ratio for reliable performance. The material is available in a wide range of widths, load capacities, and custom lengths, ensuring suitability for diverse logistics and securing requirements.

Technical Specifications

Material	100% High Tenacity Polyester
Width	25mm to 300mm
Safety Factors	4:1, 5:1, 6:1, 7:1, 8:1
Standard	EN1492

Load Capabilities

Working Load Limit (W.L.L.)

1 Ton

Minimum Capacity

12 Ton

Maximum Capacity

Configurations

Lifting Eye Configurations

- Flat Eye
- Reversed Eye
- Folded Eye 1/2 Width from 1 Side
- Folded Eye 1/2 width from 2 sides
- Folded Eye 1/3 width

Ply Options

Single ply, Double ply, Four ply